

4924

9723896 AG, AH, AJ

RA16765-67

MATERIAL SAFETY DATA SHEET

Product Name: Potter's Choice (Copper)	Product Code: PC Series - Copper
Manufacturer: American Art Clay Co. 6060 Guion Road Indianapolis, IN 46254	
Information Number: (800) 374-1600	Emergency Number: (800) 374-1600

Section I – Product Identification

Product Name: Potter's Choice	Product Class: Ceramic Glaze	Product Size: 16 oz. Gal, 25 lbs
PC 1, 2, 4, 25, 40, 41, 42, 46, 49		

Section II – Hazardous Ingredients

Reportable Components	CAS#	Vapor Pressure Mm Hg @ Temp	Weight Percent
Copper Carbonate	7492-68-4		
Soluble Copper	1mg/m3 @ CU		
Water	7732-18-5		
Sodium Borosilicate Frit	65997-18-4		
Clay	1332-58-7		
Crystalline Silica	14808-60-7		

This product carries the CL Seal. Contains soluble copper. See Section VI for further information.
Labeling conforms to ASTM D4236.

Section III – Physical / Chemical Characteristics

Boiling Range: NA	Specific Gravity (H2O=1): Less than 2.
Vapor Density: NA	Evaporation Rate: NA
Coating V.O.C.: NA	Material V.O.C.: NA
Appearance and Odor: Liquid	

Section IV – Fire and Explosion Hazard Data

Flash Point: NA	Method Used: NA
Flammable Limits in Air by Volume: NA- Lower	NA – Upper
Extinguishing Media: NA	
Special Firefighting Procedures: No fire hazard.	
Unusual Fire and Explosion Hazards: No fire hazard.	

Section V – Reactivity Data

Stability: Stable	Conditions to Avoid: None
Incompatibility (Materials to Avoid): None	
Hazard Decomposition or Byproducts: Will not occur.	
Hazardous Polymerization: Will not occur.	

MATERIAL SAFETY DATA SHEET

Product Name: Potter's Choice (Copper)

Product Code: PC Series - Copper

Manufacturer: American Art Clay Co.
6060 Guion Road
Indianapolis, IN 46254

Information Number: (800) 374-1600

Emergency Number: (800) 374-1600

Section I – Product Identification

Product Name: Potter's Choice

Product Class: Ceramic Glaze

Product Size: 16 oz.
Gal, 25 lbs

PC 1, 2, 4, 25, 40, 41, 42, 46, 49

Section II – Hazardous Ingredients

Reportable Components	CAS#	Vapor Pressure Mm Hg @ Temp	Weight Percent
Copper Carbonate	7492-68-4		
Soluble Copper	1mg/m3 @ CU		
Water	7732-18-5		
Sodium Borosilicate Frit	65997-18-4		
Clay	1332-58-7		
Crystalline Silica	14808-60-7		

This product carries the CL Seal. Contains soluble copper. See Section VI for further information.
Labeling conforms to ASTM D4236.

Section III – Physical / Chemical Characteristics

Boiling Range: NA
Vapor Density: NA
Coating V.O.C.: NA
Appearance and Odor: Liquid

Specific Gravity (H2O=1): Less than 2.
Evaporation Rate: NA
Material V.O.C.: NA

Section IV – Fire and Explosion Hazard Data

Flash Point: NA
Flammable Limits in Air by Volume: NA- Lower
Extinguishing Media: NA
Special Firefighting Procedures: No fire hazard.
Unusual Fire and Explosion Hazards: No fire hazard.

Method Used: NA
NA – Upper

Section V – Reactivity Data

Stability: Stable
Incompatibility (Materials to Avoid): None
Hazard Decomposition or Byproducts: Will not occur.
Hazardous Polymerization: Will not occur.

Conditions to Avoid: None