

9739899  
9739897  
9739898

9739895  
9739896

DUO Painting Oil Medium - 1 / 3

7363



2016-10-31

## SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910. 1200. Standard must be consulted for specific requirements.

U.S. Department of Labor  
Occupational Safety and Health Administration  
(Non-Mandatory Form)  
OMB No.1218-0072

### § 1 - IDENTITY INFORMATION

Product Name (as used on label and list) :

DO 655, DO 505, DO 405 DUO Painting Oil Medium

Manufacturer : HOLBEIN Works, Ltd.

Address : 2-2-5, Ueshio, Chuo-ku, Osaka-shi  
OSAKA 542-0064 JAPAN

Telephone Number for information : 81-6-6191-7722

Emergency Telephone Number : 81-72-985-1221

Preparer : ALAKI, Yutaka

### § 2 - HAZARD IDENTIFICATION

Classification : Flammable Liquid, Category 3  
Hazard information : Irritant to eyes and skin. Inhalation of concentrated vapor irritates eyes and/or bronchial pathway, or may influences to central nerve.  
Acute toxicity : Category 4  
Skin Irritation : Category 3  
Eye Effects : Category 2B  
Respiratory Sensitization : Category 1/Inhalation may cause allergy, asthma or dyspnea.  
Skin Sensitization : Category 1/Inhalation may cause allergic dermatitis.



### § 3 - COMPOSITION / INGREDIENTS

Components (Specific Chemical Identity, Common Name(s), C.I. No)	CAS. No.
Polymerized Linsced Oil *	67746-08-1
Synthetic Resin	69430-35-9
Solvent (Naphtha, Hydrated Heavy Petroleum)	64742-48-9
Dryer (Metallic soap, Ex; Cobalt Naphthenate, (RCOO) <sub>2</sub> Co)	61789-51-3
Surfactant	Registered

\*: Vegetable drying oil (Triglyceride of Linolic, Linolenic, Oleic and/or Palmitic acid)

### § 4 - FIRST AID MEASURES

Inhalation : Remove to fresh air.  
Ingestion : Do NOT induce vomiting, except in case of excess swallowing.  
Ask immediately for medical doctor.  
Eyes : In case of eye contact, rinse with plenty of water and if necessary consult an eye specialist.  
Skin Contact : Upon skin contact, wash with water, soap or other non-irritating cleansing agents.

---

**§ 5 - FIRE AND EXPLOSION HAZARD DATA**

Flammability : Combustible  
Flash Point : 44.3 °C  
Autoignition Temp : 263°C  
Extinguishing Method : Take off fire or other flammable materials, and use with extinguishing tools.  
Extinguishing Media : Foam, Dry powder, CO2  
Unusual Fire and Explosion Hazards : None

---

**§ 6 - ACCIDENTAL RELEASE MEASURES**

Step to Be Taken in Case Material Is Released or Spilled : Take up with absorbent materials.  
Prevention of Secondary Disaster : Take off fire or other flammable materials.  
Personal Consideration : Use mechanical ventilation  
Environmental Precautions : Prevent spills from entering storm sewers or drains.

---

**§ 7 - HANDLING AND STORAGE**

Precautions to Be Taken in Handling and Storing : Avoid prolonged or repeated contact with skin and eyes.  
Storage Requirements : Keep from fire or flammable materials. Do not allow product temperature to rise high.  
Handling Procedures/Equipment : Treat as paint product.

---

**§ 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

Engineering Controls : Use mechanical ventilation when applying.  
Personal Protection : Avoid inhaling aerosols.

---

**§ 9 - PHYSICAL / CHEMICAL CHARACTERISTICS**

Appearance : Clear yellow liquid  
Odor : Mild petroleum smell  
pH : N/A  
Boiling Point : 156~200 °C  
Specific Gravity (H2O = 1) : 0.84  
Solubility in Water : Dispersible

---

**§ 10 - HAZARD INFORMATION AND STABILITY**

Physical Dangers : Combustible  
Stability : Stable under normal state  
Reactivity : None  
Byproducts : Carbon dioxide, water and dioxide of cobalt.  
Hazardous Decomposition or Byproducts : In case of fire, forms carbon dioxide and water.  
Incompatibility (Materials to Avoid) : None  
Corrosive Behavior : None

---

**§ 11 - TOXICOLOGICAL INFORMATION**

Primary Routes of Entry : Dermal, swallowing  
Oral Toxicity (LD50) : 20 g/kg  
Inhalation Toxicity : Inhalation of concentrated vapor irritates eyes and/or bronchial pathway, induces dizziness or headache, or influences to central nerve.  
Effects of Acute Exposure : None known  
Eye irritation : Usually irritant to the eye mucous membrane



Skin irritation : Long time or repeated contact may irritate to skin and may cause inflammation.

Repeated Exposure : Inhalation of mist may cause irritation of bronchial pathway and/or stupor.

Sensitization, Reproductive Toxicity : No data available on product.

Mutagenicity, Carcinogenicity, Teratogenicity : No data available

---

#### § 12 - ECOLOGICAL INFORMATION

Not been confirmed

---

#### § 13 - DISPOSAL CONSIDERATIONS

Disposal Considerations : To be incinerated.

Waste Disposal Method : Stained cloths or papers which has been used to wipe or so on are so flammable that they had better been wetted with water.

---

#### § 14 - TRANSPORT INFORMATION

Hazard Class : Class 3 (Flammable)

UN number : 1268

---

#### § 15 - REGULATORY INFORMATION

Conforms to ACMI, Art & Creative Materials Institute, under ASTM D 4236

Industrial Safety and Health Law : Flammable organic solvent

Fire Service Law : Dangerous Materials ; Group 4, Petroleum Category 2

Regulation to Control Dangerous Materials : Conforms to article 41 and below.

High Pressure Gas Safety Law : N/A

---

#### § 16 - OTHER INFORMATION

Notice: The information of this sheet is based on the present state of our knowledge and does not therefore guarantee certain properties.

---

#### Appendix

##### Table HEALTH INFORMATION

DUO Painting Oil is classified as CL product in the ACMI system.

AP (Approved Product) : Contain no materials in sufficient quantities to be toxic or injurious to humans.

CL (Cautionary Label) : Any known health risks and with information on the safe and proper use of these materials